

PCC #: \_\_\_\_\_

BILL TO: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

SHIP TO:  SAME AS BILLING \_\_\_\_\_

ADDRESS: \_\_\_\_\_

SHIPPING:  GROUND (FXGD)  STANDARD 2 DAY (FX2D)  
OVERNIGHT:  PRIORITY (FX1D)  1st OVERNIGHT (FX1A)  
 OTHER: \_\_\_\_\_

CLINICIAN: \_\_\_\_\_

CELL #: \_\_\_\_\_

PATIENT ID: \_\_\_\_\_

HEIGHT: \_\_\_\_\_ WEIGHT: \_\_\_\_\_ AGE: \_\_\_\_\_

MALE  FEMALE  
 LEFT  RIGHT  BILATERAL

NG ENCOUNTER #: \_\_\_\_\_

MEASUREMENT DATE: \_\_\_\_\_

IN-OFFICE REQUEST DATE & TIME: \_\_\_\_\_

Click here to email form > [HFN\\_Arizona@Hanger.com](mailto:HFN_Arizona@Hanger.com) CUSTOMER SERVICE PHONE: 480-894-1755

**MEASUREMENTS TAKEN IN**

CM  IN

**DEVICE TYPE**

AmpuShield w/Semi-Rigid Frame\*\*

Soft Protector  
w/Posterior 1/8" Kydex stay

Rigid PE Protector

Unlined, top 1/8" Pelite padding

Add Flared Top

Lined with 1/4" Aliplast

Add Flared Top

**DISTAL END PAD\***

Ships w/additional 1" adjustment pad

Standard (1")

Other \_\_\_\_\_ IN

**ADDITIONAL ITEMS**

Extra End Pad Set

**VARIATION**

Ventilate

**Knee Flexion**

<input type="checkbox"/>	<input type="checkbox"/>
Left	Right


• Flexion angles greater than 20 degrees requires a rigid protector with step locks. Device will be designed neutral and can be adjusted at fitting.

**Varus**

<input type="checkbox"/>	<input type="checkbox"/>
Left	Right

**Valgus**

<input type="checkbox"/>	<input type="checkbox"/>
Left	Right



**\*IMPORTANT:** Provide trim length from MPT.  
\*\*Must be a minimum of 8" for Semi-Rigid Frame. Fabrication will adjust distal length to accommodate for end pad.

- |                          |                          |
|--------------------------|--------------------------|
| Left                     | Right                    |
| <input type="checkbox"/> | <input type="checkbox"/> |
| 10"                      |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| 8"                       |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| 6"                       |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| 4"                       |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| 0 Lvl                    |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| -2"                      |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| -4"                      |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| -6"                      |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| -8"                      |                          |
| <input type="checkbox"/> | <input type="checkbox"/> |
| -10"                     |                          |

**MPT to Finished Length\*\***

<input type="checkbox"/>	<input type="checkbox"/>
Left	Right

**0 - MPT Level**

**MPT to Distal End**

<input type="checkbox"/>	<input type="checkbox"/>
Left	Right

**TURNAROUND TIMES**

To review current projected turnaround times for fabrication sites visit the [Daily HFN Capacity Webpage](#).