



HFN Phoenix

302 E University Dr, Ste 301 • Phoenix, AZ 85004 P 480.894.1755 | F 480.921.9686 | E HFN_Arizona@Hanger.com

Warranty:

The frame and Mackie hinge of your brace are covered by a one year limited warranty against defects in materials or craftsmanship soft goods are covered by a six month limited warranty.

Ortho Innovations' Custom Fabricated Products Order Form

Date		Date Nee	ded	F	P.O. #	
BILLING INFORMATION						
Facility		Contact N	lame			
Billing Address						
City		State		-	Zip	
Phone		Fax				
SHIPPING INFORMATION						
Facility		Shipping Address				
City		State Zip				
Phone		Fax				
	ndard 2 Day (FX2D)	O Priority (I	FX1D)	🔵 1st Overnig	iht (FX1A)	Dther
PATIENT INFORMATION						
Name				Height	Weight	Age
Physician						
Special Instructions:						
Important Note: If a patient presents we ordering a custom brace, the device cat the board at the joint center.						
Custom Fabricated Elbow Extension Brace – with removable knob		Custom Fabricated Knee Extension Brace – with removable knob How to measure for a Custom Knee Brace:				
How to measure for a Pre-fabricated Elbow Brace:						

- 1. Facing the patient, position the elbow in maximum extension and the wrist in neutral pronation/supination. See diagram to check proper positioning for measurement.
- 2. A circumference measurement should be taken around the arm at each level.
- 3. A diameter, medial to lateral (M-L) measurements, is also needed at each level.
- Level A is located 7 inches above joint center.
- Level B is located at the joint center. M-L should be taken in line with the humeral condyles and reflect the widest M-L.
- Level C is located 7 inches below joint center.


Patient's Measurements for Custom Elbow Brace


Affected Elbow: LEFT or RIGHT Knob Placement: MEDIAL or LATERAL

Standard Overall Length = 14 inches (specify if other):

Humeral Section:	Forearm Section:







- . Patient may be seated or lying down for measurements. Position leg in maximum extension.
- 2. A circumference measurement is the distance around the leg and should be taken at each level.
- 3. A diameter, medial to lateral (M-L) measurements, is the width of the leg and is needed at each level.
- Level A is located 10 inches above joint center.
- Level B is located at the joint center. M-L should be taken in line with mid patella and reflect the widest M-L.
- Level C is located 10 inches below joint center.

Patient's Measurements for Custom Knee Brace

 Affected Knee:
 LEFT or RIGHT

 Standard Overall Length = 20 inches (specify if other):

 Thigh Section:
 Calf Section:

 (10" Standard)
 (10" Standard)

	Circumference		M-L		
LEVEL A	A	"	\mathbb{A}		'
LEVEL B	B	"	B		'
LEVEL C	©	"	\bigcirc		,

		ß	سل متركم لمديد لي
A	▶	$ ^{2}$	Level A
	10″		/
B B	•••		Level B
©	10″	197	
	-	• \ /	Level C
		ų.	
		1 3421	